REPAIRABILITY INDEX CALCULATION AND PRESENTATION OF THE PARAMETERS WHICH ALLOWED TO ESTABLISH IT

Pressure cleaner

Date of calculation	2025-08-04		
Manufacturer's or importer's name or trademark	AVA of Norway AS		
Manufacturer or importer adress	Nøstetorget 5, 5011 Bergen		
Manufacturer's or importer's model identifier	10-100-239		

This "FINAL_SCORE" tab in English is purely indicative. In order to meet Belgian legal obligations, please select simultaneously the following 3 tabs "NOTE_FINALE" + "FINALE_SCORE" + "FINAL_SCORE_DE", and print as pdf. This will produce a pdf with the sub score information sheet in French, Dutch and German. Store this pdf on your website. Please send the URL and a QR code pointing to this pdf to the importers/vendors/distributors.

Criteria	Sub-criteria	Score of subcriterion /10	Weighting factor of subcriterion	Score of criterion /20	Total criteria scores /100
CRITERION 1: DOCUMENTATION	${\bf 1.1} \ Availability \ of the technical documentation and other documentation related to user and maintenance instructions$	10,0	2	20,0	
DISASSEMBLY, ACCESSIBILITY, TOOLS,	2.1 Ease of disassembly parts from List 2*	10,0	1	1	
	2.2 Necessary tools (List 2)	10,0	0,5	20,0	
	2.3 Fasteners characteristics parts from List 1** and List 2	10,0	0,5		
CRITERION 3 : AVAILABILITY OF SPARE - PARTS	3.1 Availability over time parts from List 2	10,0	1		95,0
	Availability over time parts from List 1 10,0		0,5	20,0	00,0
	3.3 Delivery time parts from List 2	10,0	0,3	20,0	
	3.4 Delivery time parts from List 1	10,0	0,2		
CRITERION 4: PRICE OF SPARE PARTS	4. Ratio between price of parts from list 2 to the price of the product	7,5	2	15,0	
CRITERION 5: SPECIFIC CRITERION	5.1 Free remote assistance	10,0	2	20,0	
Reparability index on 10					9,5

^{*} list 2: list of a maximum of 3 to 5 spare parts (depending on the category of equipment concerned) whose broken or malfunctioning parts are the most frequent;
** list 1: list of a maximum of 10 other spare parts (depending on the category of equipment concerned) whose good condition is necessary for the operation of the equipment.