

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: SPL

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

Model identifier: L145128027

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E14		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	280 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode power (P_{on}), expressed in W	3,3	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, light-	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,463 0,414	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	-3	Survival factor	0,90	
the lumen maintenance factor	0,90			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	5	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	0,3	Stroboscopic effect metric (SVM)	0,3	

(a) : not applicable;

(b) : not applicable;

SPL Spectrum Test Report

Sample :
Specification : E14 4W Dim
Sample No. : E14 4W Dim 01
Manufacturer :


Date : 2021-05-27 11:35:19
Sam. Status :
Instrument : HaasSuite(EVERFINE)
Test by : Schiefer
Assessor : damin

Test Condition

Temperature : 25.3Deg
WL Range : 380nm-780nm
Test Mode : Fast Test

RH : 65.0%
IP : 50711 (77%)
T : 72 ms
Sensitivity : High

Spectrum



Colorimetric Parameters

Chromaticity Coordinate: $x = 0.4634$ $y = 0.4149$ / $u' = 0.2629$ $v' = 0.5295$ ($duv=1.28e-03$)

CCT= 2684K Prcp WL: $L_d=583.9nm$ Purity=63.6%

Peak WL: $L_p=605nm$ FWHM: $=107.5nm$ Ratio: R=24.9% G=72.6% B=2.4%

Render Index: $R_a = 80.1$

R1 =79 R2 =92 R3 =92 R4 =76 R5 =79 R6 =92 R7 =79

R8 =52 R9 =-3 R10=83 R11=76 R12=77 R13=82 R14=96 R15=69

LEVEL:OUT WHITE:ANSI_2700K

Photometric & Radiometric Parameters

Flux = 279.06 lm Eff. : 84.10 lm/W Fe = 846.79 mW


Electrical parameters

V = 230.0 V I = 0.01626 A P = 3.318 W PF = 0.8874

Schiefer Professional Lighting

www.spl-lighting.com

Model placed on the Union market from 07/07/2021



EPREL registration number: 842139

<https://eprel.ec.europa.eu/qr/842139>

Supplier: Schiefer Signaal Speciaallampen B.V. (Importer)

Website: www.schiefer.nl

Customer care service:

Name: Schiefer Lighting

Website: www.schiefer.nl

Email: info@schiefer.nl

Phone: +31765037717

Address:

Potterbakkerstraat 35

4871EP Etten-Leur

Netherlands