Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Baseline

Supplier's address: Customer support, Herikerbergweg 336 - Diana building, 1101 CT Amsterdam,

NL

Model identifier:	10495584
-------------------	----------

_		•			
11/1	ഘ	Λt	liont	sourc	Ά.
	~	v	115111	3041	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters				
Parameter		Value	Parameter	Value
		General product p	arameters:	
	nption in on- 00 h), rounded st integer	4	Energy efficiency class	D
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	470 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pow pressed in W	ver (P _{on}), ex-	3,4	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without	Height Width	107 60	Spectral power distribution in the	See image in last page
separate con- trol gear, light-	Depth	60	range 250 nm to 800 nm, at full-load	

ing control parts and non-lighting control parts, if any (millimetre)					
Claim of equivalent power ^(a)		Yes	If yes, equivalent power (W)	40	
			Chromaticity coordi-	0,458	
			nates (x and y)	0,410	
Parameters for I	LED and OLED lig	ht sources:			
R9 colour render	ring index value	0	Survival factor	0,90	
the lumen maintenance factor		0,96			
Parameters for I	Parameters for LED and OLED mains light sources:				
displacement fac	ctor (cos φ1)	0,00	Colour consistency in McAdam ellipses	6	
Claims that an L replaces a flu source without last of a particula	orescent light integrated bal-	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (P	st LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

Model placed on the Union market from 10/06/2025



EPREL registration number: 2384185 https://eprel.ec.europa.eu/qr/23

84185

Supplier: Maxeda DIY Group B.V. (Manufacturer) Website: https://www.maxedadiygro

up.com/

Website:

Customer care service:

Name: Customer support

Email: Customersupport@diymaxeda.com Phone: +203983333

Address:

Herikerbergweg 336 - Diana building

1101 CT Amsterdam

Netherlands