

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Lybardo

**Supplier's address:** Ledlampenkopen.nu, Houtzagerijstraat 11, 5451 HZ Land van Cuijk Cuijk Brabant, NL

**Model identifier:** A6021HDS

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	E27		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

## Product parameters

Parameter	Value	Parameter	Value
-----------	-------	-----------	-------


### General product parameters:

Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	2	Energy efficiency class	G
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	50 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 200
On-mode power ( $P_{on}$ ), expressed in W	2,8	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	0,00
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimensions without separate control gear, light-	Height	108	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	60	
	Depth	108	
			See image in last page

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,515 0,421
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	68	Survival factor	-
the lumen maintenance factor	-		
<b>Parameters for LED and OLED mains light sources:</b>			
displacement factor (cos $\phi_1$ )	0,30	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a): not applicable;

(b): not applicable;



Spectral Distribution

Model placed on the Union market from 28/10/2021



**EPREL registration number:** 1033042

<https://eprel.ec.europa.eu/qr/1033042>

**Supplier:** Ledbuydirect B.V. (Importer)

**Website:** [www.ledlampenkopen.nu](http://www.ledlampenkopen.nu)

**Customer care service:**

**Name:** Ledlampenkopen.nu

**Website:** [www.ledlampenkopen.nu](http://www.ledlampenkopen.nu)

**Email:** [info@ledlampenkopen.nu](mailto:info@ledlampenkopen.nu)

**Phone:** 0485318675

**Address:**

Houtzagerijstraat 11  
5451 HZ Cuijk  
Netherlands